

MEMS Capacitive Accelerometer

ASC OS-325MF-PG

Triaxial

MEMS Capacitive

Measurement Range: ± 2 to ± 200 g

Noise Density: 10 to 680 $\mu\text{g}/\sqrt{\text{Hz}}$

Frequency Range ($\pm 5\%$): DC to 2900 Hz

Stainless-Steel Housing (IP68)

Made in Germany



MEMS Capacitive Accelerometer

The key components in capacitive accelerometers are high-quality micro-electro-mechanical systems (MEMS) that feature excellent long-term stability and reliability. This technology enables the measurement of static (DC) and constant accelerations, which can be used to calculate the velocity and displacement of moving objects. Depending on the design of the spring-mass-damping system, however, it is also possible to detect dynamic (AC) accelerations with amplitudes up to ± 200 g and within a frequency response range of up to 2.9 kHz ($\pm 5\%$) or 7 kHz (± 3 dB). Other advantages of capacitive accelerometers are their outstanding temperature stability, excellent response behavior and achievable resolution.

Description

The accelerometers of type ASC OS-325MF-PG are based on proven MEMS technology and capacitive operating principle. The integrated electronic circuitry enables a differential analog voltage output (± 2.7 V FSO) and flexible power supply voltage from 5 to 40 VDC. The MF (Medium Frequency) accelerometers from ASC provide a wide frequency response range from 0 Hz to 7 kHz (± 3 dB) and an extremely robust design with shock resistance up to 6,000 g.

The sensors feature a robust, reliable stainless-steel housing with protection class IP68 and an integrated cable with configurable length and connectors.

The hermetically sealed housing of the accelerometers is ideal for very harsh environmental conditions, e.g. bogie stability tests and monitoring applications in rail transport or condition monitoring of vehicles and their components in the construction sector.

Features

- Low Noise Differential Voltage Output
- DC Response, Gas damped
- Very High Shock Resistance
- Excellent Offset and Scale Factor Stability


Options

- Customized Cable Length
- Customized Connector
- TEDS Module
- V4A Stainless-Steel Housing

Applications

- Railway Engineering
- Condition Monitoring
- Structural Health Monitoring

More applications in several markets are figured out on our web page www.asc-sensors.de



Typical Specification

Dynamic

Measurement Range	g	±2	±5	±10	±30	±50	±100	±200
Scale Factor (sensitivity)	mV/g	1350	540	270	90	54	27	13.5
Noise Density	µg/√Hz	10	20	35	100	170	340	680
Frequency Response Range (±5 %)	Hz	0 to 700	0 to 1150	0 to 2000	0 to 2300	0 to 2700	0 to 2900	0 to 2500
Frequency Response Range (±3 dB)	Hz	0 to 1150	0 to 1900	0 to 3200	0 to 4000	0 to 4500	0 to 5000	0 to 7000
Amplitude Non-Linearity	% FSO	<0.1 (typ) <0.3 (max)						
Transverse Sensitivity	%	<1						

Electrical

Power Supply Voltage	V	5 to 40						
Operating Current Consumption	mA	<10						
Offset (bias)	mV	±10						
Broadband Noise (over frequency range ±5 %)	µV	250	310	410	440	475	490	460
Resistive Load	kΩ	1000						
Isolation		Case Isolated						

Environmental

Temperature Coefficient of the Scale Factor	ppm/K	120 (typ) 20 to 220 (max)						
Temperature Coefficient of the Offset (max)	mg/K	±0.2	±0.5	±1	±3	±5	±10	±20
Operating Temperature Range	°C	Standard Cable: -40 to +100 Optional with seawater resistant Cable K3: -15 to +70						
Storage Temperature Range	°C	-55 to +125						
Shock Limit (0.1 ms, half-sine)	g	6000						
Protection Class		IP68 (test conditions: hydrostatic head 3 m, duration 30 min, DUT powered) Please note: the housing is hermetically sealed and therefore not repairable.						

Physical

Sensing Element		MEMS Capacitive						
Case Material		Standard: Stainless-Steel V2A (material number 1.4301) Optional: Stainless-Steel V4A (seawater resistant, material number 1.4404)						
Connector at Cable End		Optional						
Mounting		Adhesive Screw Holes						
Weight (without cable)	gram	68						
Cable (standard)		30 gram per meter AWG 30 Polyurethane (PUR) Diameter 4.5 mm						
Cable K3 (seawater resistant)		22 gram per meter AWG 30 Polyurethane (PUR) Diameter 3.75 mm waterproof, sea water resistance up to +60°C and 1 bar pressure						

Sensor Calibration

Factory Calibration (supplied with the sensor)

Part Number		#16723	#16755	#16757	#16759	#16761	#16763	#16765
Measurement Range (sensor)	g	±2	±5	±10	±30	±50	±100	±200
Applied Frequency (min)	Hz	1	10	10	10	10	10	10
Applied Frequency (max)	Hz	100	1150	2000	2300	2700	2900	2500
Input Amplitude	m/s ²	5	5	50	100	200	200	200
Reference Frequency for Determination of Scale Factor	Hz	16	80	80	80	80	80	80

Calibration according DIN ISO 17025 (order separately)

Part Number		#16739	#16767	#16769	#16771	#16773	#16775	#16777
Measurement Range (sensor)	g	±2	±5	±10	±30	±50	±100	±200
Applied Frequency (min)	Hz	0.5	10	10	10	10	10	10
Applied Frequency (max)	Hz	150	1900	3200	4000	4500	5000	7000
Input Amplitude	m/s ²	5	5	50	100	200	200	200
Reference Frequency for Determination of Scale Factor	Hz	16	80	80	80	80	80	80

Remarks:

- The conversion factor 1 g corresponds to 9.80665 m/s².
- If any other calibration procedure is required, don't hesitate to contact us. Our services include both factory calibration and calibration in accordance with DAkkS guidelines.
- Furthermore, sensors have to be calibrated regularly to ensure accurate and precise results. On request we will be glad to remind you of the next scheduled calibration of your sensors.

Standard Cable Code / Pin Configuration (12 Wire System) including separate Power Supply for all Axes

	Pin	Color Code	Description
1	Supply +	Red/Violet	X-Axis: power supply voltage +5 to +40 VDC
2	Supply -	Black/Violet	X-Axis: power GND
3	Signal +	Green/Violet	X-Axis: positive, analog output voltage signal for differential mode
4	Signal -	White/Violet	X-Axis: negative, analog output voltage signal for differential mode
5	Supply +	Red/Grey	Y-Axis: power supply voltage +5 to +40 VDC
6	Supply -	Black/Grey	Y-Axis: power GND
7	Signal +	Green/Grey	Y-Axis: positive, analog output voltage signal for differential mode
8	Signal -	White/Grey	Y-Axis: negative, analog output voltage signal for differential mode
9	Supply +	Red	Z-Axis: power supply voltage +5 to +40 VDC
10	Supply -	Black	Z-Axis: power GND
11	Signal +	Green	Z-Axis: positive, analog output voltage signal for differential mode
12	Signal -	White	Z-Axis: negative, analog output voltage signal for differential mode

MEMS Capacitive Accelerometer

Standard Cable Code / Pin Configuration (8 Wire System) including common Power Supply for all Axes

Pin	Color Code	Description	
1	Supply +	Red	Power: supply voltage +5 to +40 VDC
2	Supply -	Black	Power: GND
3	Signal +	Green/Violet	X-Axis: positive, analog output voltage signal for differential mode
4	Signal -	White/Violet	X-Axis: negative, analog output voltage signal for differential mode
5	Signal +	Green/Grey	Y-Axis: positive, analog output voltage signal for differential mode
6	Signal -	White/Grey	Y-Axis: negative, analog output voltage signal for differential mode
7	Signal +	Green	Z-Axis: positive, analog output voltage signal for differential mode
8	Signal -	White	Z-Axis: negative, analog output voltage signal for differential mode

Optional Cable Code / Pin Configuration (8 Wire System)

Pin	Color Code Cable Type K3	Description	
1	Supply +	Red	Power: supply voltage +5 to +40 VDC
2	Supply -	Brown	Power: GND
3	Signal +	White	X-Axis: positive, analog output voltage signal for differential mode
4	Signal -	Grey	X-Axis: negative, analog output voltage signal for differential mode
5	Signal +	Yellow	Y-Axis: positive, analog output voltage signal for differential mode
6	Signal -	Pink	Y-Axis: negative, analog output voltage signal for differential mode
7	Signal +	Green	Z-Axis: positive, analog output voltage signal for differential mode
8	Signal -	Blue	Z-Axis: negative, analog output voltage signal for differential mode

Cable Configuration

8 Wire System - 8L

Common power supply for all axes, no cable switch




12 Wire System - 12L (standard cable only)

Separate power supply for all axes, no cable switch




8 Wire System - 8L3

Common power supply for all axes, including cable switch



12 Wire System - 12L3 (standard cable only)

Separate power supply for all axes, including cable switch



Ordering Information

Series	Model	- Range [g]	- Cable Length [m]	Connector & Pinout	- Cable	- Cable Configuration
ASC OS	-325MF-PG	002	6	A	K3	8L
		005				8L3
		010				12L
		030				12L3
		050				
		100				
		200				

Example:

ASC OS-325MF-PG-002-6A-8L

Ordering information are based on standard configurations. All customized versions regarding connector and/or pinout will lead to a corresponding product match code:

- Standard length of the integrated cable is 6 meters. However, different customized cable lengths for all types of cables are possible on request.
- All versions have no connector at the cable end which is identified by "A" in the product match code. However, it is possible to assemble almost all connector types during production.
- Cable type identifier "K3" is not used within the ordering information when standard cable is requested.
- Applications where waterproof accelerometers are required, cable type K3 is suggested.
- Applications where seawater resistant accelerometers are required, cable type K3 is mandatory. In this case also the optional stainless-steel housing V4A (material number 1.4404) is recommended.
- Cable configurations "12L" and "12L3" are only available when the standard cable is used.

Safety Precaution for Installing and Operating

This data sheet is a part of the product. Read the data sheet carefully before using the product and keep it available for future operation. Handling, electrical connections, mounting or any other work performed at the sensor must be carried out by authorized experts only. Appropriate safety precautions must be taken to exclude any risk of personal injury and damage to operating equipment as a result of a sensor malfunction.

Handling

The sensor is packaged in a reliable housing to protect the sensing elements and integrated electronic components from the ambient environment. However, poor handling of the product can lead to damages that may not be visible and cause electrical failure or reliability issues. Handle the component with caution:

- Avoid shocks and impacts on the housing, such as dropping the sensor on hard surface
- Never move the sensor by pulling the cable
- Make sure that the sensor is used within the specified environmental conditions
- Transport and store the sensor in its original or similar packaging
- The sensor should be mounted on a stable flat surface with all screws tightened or other mounting options
- When adhesives are used to mount the sensors, please select the corresponding products according to permanent or removable mounting, ambient temperature range as well as quality of the mounting surface
- Avoid any deformation during mounting the sensor
- Mounting tolerances may have an influence on the measured result

Electrical

ASC's inertial sensors are working with many established data acquisition systems. However, make sure that a proper DAQ is used, for the corresponding operation principle of the sensor. Furthermore, suitable precautions shall be employed during all phases of shipment, handling and operating:

- Active sensor pins are susceptible to damage due to electrostatic discharge (ESD)
- Make sure that the sensor is used within the specified electrical conditions
- Check all electrical connections prior to initial setup of the sensor
- Completely shield the sensor and connecting cable
- Do not perform any electrical modifications at the sensor
- Do not perform any adaptations on the wiring or connectors while the device under power
- Never plug or unplug the electrical connection while the sensor is under power
- When a certain pin is not used during operation, make sure that the pin is insulated

Quality

- We have a quality management system according to ISO 9001:2015.
- The Deutsche Akkreditierungsstelle GmbH (DAkkS) has awarded to our calibration laboratory the DIN EN ISO/IEC 17025:2018 accreditation for calibrations and has confirmed our competence to perform calibrations in the field of mechanical acceleration measurements. The registration number of the certificate is **D-K-18110-01-00**.
- All ASC products are **CE**-compliant.

Made in Germany



analyzing



monitoring



testing



measuring