

Crash test accelerometer



Description




Model **H30** is a miniature triaxial accelerometer designed for crash testing that require minimal mass weight and a wide frequency response. The accelerometer meets SAE J211 specifications for instrumentation for impact testing. It is available in four different acceleration ranges, 500g, 2000g, 6000g and 20000 g full scale. The tri-axial accelerometer is based on a latest piezo-resistive MEMS sensing element, which offers exceptional dynamic range and stability. This unit features the full bridge output configuration with a compensated temperature range from 0 to +50° C. Model H30 accelerometer has a standard transverse sensitivity accuracy of <3%. Advance MEMS structure provides outstanding shock survivability, a flat amplitude and phase response up to 7kHz.

Features

- Water proof
- DC response
- Miniature tri-axial
- Shock, low & high frequency
- 10K g shock survivability
- 2-10Vdc Excitation
- Integrated 1 to 3 cable

Application

- Auto crash test
- On vehicle shock test
- Drop test



Specification

All values are typical at +24°C (+75°F), 100Hz, and 10Vdc excitation unless otherwise stated.

DASH No.	-05K	-2K	-6K	-20k	UNITS
Dynamic Range	±500	±2000	±6000	±20000	g
Sensitivity	0.4	0.15	0.1	0.05	mV/g
Frequency Response ±5% (Z-axial)	0-3000	0-4000	0-5000	0-10000	Hz
Frequency Response ±5% (X/Y-axial)	0-2000	0-3000	0-5000	0-10000	Hz
Frequency Response ±1dB	0-4200	0-7000	0-7000	0-15000	Hz
Phase Response ±5°	0-1000	0-2000	0-2000	0-10000	Hz
Resonant Frequency	15000	26000	26000	36000	Hz
Damping Ratio	0.3	0.05	0.05	0.02	
Shock Limit	10000	10000	10000	30000	g


PARAMETERS	VALUE	UNITS
Zero Acceleration Output	<±50	mV
Transverse Sensitivity (<1% by option)	<3	%
Non-Linearity	±1	%Reading
Thermal Zero Shift, 0-50°C (32-122°F)	±0.05 (±0.03)	%FSO/°C (%FSO/°F)
Thermal Sensitivity Shift, 0-50°C (32-122°F)	±0.1 (±0.06)	%/°C (%/°F)
Excitation Voltage	2 to 10	Vdc
Insulation Resistance (@100Vdc)	>100	MΩ
Input Impedance	2400 to 6000	Ω
Output Impedance	2400 to 6000	Ω
Operating Temperature	-20 to +85 (-4 to +185)	°C (°F)
Humidity	Epoxy Sealed	
Weight (Cable Not Included)	10	Grams
Mounting Torque	3 (0.3)	lb-in (Nm)

Accessories

Calibration certificate included.

Part Number	Description	Availability
PM0225	#4-40x3/4" socket head cap screws	Included
PJ0048	LEMO FGG-1B-307 connector	Optional
IN-01	Bridge piezo-resistive signal amplifier	Optional
PJ0048	LEMO FGG-1B-307 connector	Optional

Measurement configuration



Ordering information

H30	-	2K	-	8	C1
Model	-	Range	-	Cable length	Connector
H30	-	05K=500g 2K=2000g 6K=6000g 20K=20000g	-	6=6 meters 8=8 meters 9=9 meters	C*=1 to 3 cable adapter + Connector options Blank= Pig tail cable

Connector options

C1	C2	C3	C4	Blank
LEMO FGG-1B-307 Dallas Chip: DS2401	LEMO FGG-1B-307	LEMO FGG-1B-307 Dallas Chip: DS2401	LEMO FGG-1B-307	Blank
Pin1=N/C Pin2=Dallas pin2 Pin3=+OUT (Green) Pin4=+EXC (Red) Pin5=-EXC (Black) Pin6=-OUT (White) Pin7=N/C Housing=Dallas pin1=Shield	Pin1=N/C Pin2=N/C Pin3=+OUT (Green) Pin4=+EXC (Red) Pin5=-EXC (Black) Pin6=-OUT (White) Pin7=N/C Housing=Shield	Pin1=N/C Pin2=Dallas pin2 Pin3=+OUT (Green) Pin4=+EXC (Red) Pin5=-EXC (Black) Pin6=-OUT (White) Pin7=Housing=Dallas pin1=Shield	Pin1=-OUT (White) Pin2=-EXC (Black) Pin3=+EXC (Red) Pin4=+OUT (Green) Pin5= N/C Pin6=N/C Pin7= N/C Housing=Shield	No connector



FUTURE reserves the right to make changes to any products or technology herein to improve reliability, function, or design. FUTURE does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others.